

**MODEL:** PB-1408-1 **PRODUCT:** Piezo Buzzer

**EDITION:** A/2017

Soberton Inc.

### THIS SPECIFICATION APPLIES TO THE PIEZO BUZZER

### **SPECIFICATION**

Test condition: TEMP= $+25\pm2$  °C Related humidity= $65\pm5$ % Air pressure:  $860 \sim 1060$ mbar

item	unit	specification	condition	
rated voltage	DC	12.0		
operating volt	VDC	3 ~ 16		
rated current	ma	12		
sound output	dB	80	At 10cm	
resonant frequency	KHz	4000 ±500		
operating temp	°C	-20 ~ +70		
storage temp	°C	-30 ~ +80		
dimensions	mm	Ø13.8 x 7.5	see drawing attached	
weight (max)	gram	0.8		
housing material		PPO		
leading pin		pin type	See appearance drawing	
environmental		RoHS		
protection regulation				

# **RELIABILITY TEST**

item	test condition	variance after test
high temp. test	+80±2°C, 96 Hours	All original specifications must be satisfied after the test.
low temp. test	-30±2°C, 96 Hours	
humidity test	40±2℃, 93±2%RH,	
	96 Hours	
temperature cycling	-30±2°C, 30 minutes at +23°C, 15 minutes +80±2°C, 30 minutes at +23°C, 15 minutes 5 cycles	



**MODEL:** PB-1408-1 **PRODUCT:** Piezo Buzzer


**EDITION:** A/2017

Soberton Inc.


## **RELIABILITY TEST**


item test conditions		variance after test	
drop test	3 times from height of 70cm onto the surface of 10mm thick wooden board.	All original specifications must be satisfied after the test.	
vibration test	Axis test X Y and Z Duration: 30 minutes Rate: sweep from 10Hz - 55Hz -10Hz over 3 minutes Amplitude of 10mm		
solderability test  The part leads (pins) will be immersed in molten solder at 250 ±10°C for a period of 30 seconds.		After the test part will meet original specifications without any degradation in appearance and performance.	

### SPL & CURRENT CONSUMPTION VS. INPUT VOLTAGE



### **TEST METHOD**











MODEL: PB-1408-1 PRODUCT: Piezo Buzzer EDITION: A/2017

## **DIMENSION**

Tolerance: ±0.5 Unit: mm





no	item	material
1	case	PPO + 10% glassfiber
2	diaphragm	Copper + ceramic
3	wire	Enameled
4	PCB	Epoxy the CCL
5	pin	Copper
6	glue	Ероху





MODEL: PB-1408-1 PRODUCT: Piezo Buzzer EDITION: A/2017

### **PACKING**

100 Pcs per box Total 50 boxes per carton Total 5000 Pcs carton Volume: 51.5X 42X 26 cm

