



soberton inc.

ELECTRO
MAGNETIC
BUZZER

Acoustic Product Specification

Product Number: ST-1203T



Release | Revision: A / 2026

CONTENTS

This document contains the technical specifications for the electromagnetic buzzer.

Page 1
Specifications

Dimensions

Page 2
Reliability Test

Page 3
Electrical And Acoustical Measuring Condition

Typical Frequency Response Curve

Page 4
Surface Mounting Condition

Soldering Pattern

Page 5
Packing

Specifications


Item	Unit	Specifications
Rated Voltage	Vp-p	5.0
Operating Voltage	Vp-p	1 ~ 25
Rated Current	mA	Max.5 at 4.0KHz 50% duty cycle, square wave, 5 Vp-p
Sound Output	dB	Min. 75 at 4.0KHz 50% duty cycle, square wave, 5 Vp-p
Capacitance	pF	15000±30%@1KHz
Resonant Frequency	Hz	4000±500
Operating Temperature	°C	-20 ~ +70
Storage Temperature	°C	-30 ~ +80
Dimensions	mm	12.0 x12.0xH3.0
Housing Material		Black LCP
Net Weight	gram	Approx. 0.5
Environmental Protection Regulation		RoHS 2.0

Test Condition:

Temperature: 5~35°C Humidity: 45%~85%R.H Atmospheric Pressure: 860 ~1060hPa

Dimensions

Unit: mm
Tolerance: ±0.3mm Except where specified



Housing Material: Black LCP
Terminal Plate: 2 soldering pads, Tin Plating Brass



soberton inc.

ELECTRO
MAGNETIC
BUZZER

Acoustic Product Specification

Product Number: ST-1203T



Release | Revision: A / 2026

CONTENTS

This document contains the technical specifications for the electromagnetic buzzer.

Page 1
Specifications

Dimensions

Page 2
Reliability Test

Page 3
Electrical And Acoustical Measuring Condition

Typical Frequency Response Curve

Page 4
Surface Mounting Condition

Soldering Pattern

Page 5
Packing

Reliability Tests

After any of the following tests the part shall meet specifications without any degradation in appearance and performance except SPL. SPL shall meet the specifications and shall not deviate more than -10 dB from the initial value.

Standard Temperature Life Test

The part shall be subjected to 96 hours at 25±10°C.

Input rated voltage: 5 Vp-p

Resonant frequency : 4000Hz, 50% duty cycle, square wave.

High Temperature Test

The part shall be capable of withstanding a storage temperature of +80°C for 96 hours.

Low Temperature Test

The part shall be capable of withstanding a storage temperature of -30°C for 96 hours.

Humidity Test

Temperature +40°C±3°C

Relative Humidity 90% ~ 95%

Duration 48 hours and exposure to room temperature for 6 hours

Temperature Shock Test

Per cycle
60°C/1hour → 25°C/3hours → -20°C/1hour → 25°C/3hours

Total cycle 10 cycles

Drop Test

Standard packaging from 75cm

Drop on hardwood or board of 5cm thick, three sides, six plain.

Vibration Test

Vibration 1000 cycles/min.

Amplitude 1.5mm

Duration 1 hour in each 3 axes

Reflow Test

- Use recommended reflow soldering condition
1. No abnormality should be found after reflow
 2. Good soldering to meet soldering requirements

Note

Please make sure that any foreign materials (e.g. magnetic powder, washing solvent, flux, corrosive gas) do not enter the part during the production processes. Contamination may result in a loss of some or all audio output.



soberton inc.

ELECTRO
MAGNETIC
BUZZER

Acoustic Product Specification

Product Number: ST-1203T



Release | Revision: A / 2026

CONTENTS

This document contains the technical specifications for the electromagnetic buzzer.

Page 1
Specifications

Dimensions

Page 2
Reliability Test

Page 3
Electrical And Acoustical Measuring Condition

Typical Frequency Response Curve

Page 4
Surface Mounting Condition


Soldering Pattern

Page 5
Packing


Electrical And Acoustical Measuring Condition

Recommended Driving Circuit

Resonant frequency, 50% duty cycle, Square wave. Signal amplitude should be large enough to saturate the transistor.




Recommended Setting



Typical Frequency Response Curve

5.0Vp-p, 50% duty cycle, square wave, 10cm





soberton inc.

ELECTRO
MAGNETIC
BUZZER

Acoustic Product Specification

Product Number: ST-1203T



Release | Revision: A / 2026

CONTENTS

This document contains the technical specifications for the electromagnetic buzzer.

Page 1
Specifications

Dimensions

Page 2
Reliability Test

Page 3
Electrical And Acoustical Measuring Condition

Typical Frequency Response Curve


Page 4
Surface Mounting Condition

Soldering Pattern

Page 5
Packing


Surface Mounting Condition

Reflow soldering
Recommendable reflow soldering condition is as follows.



- Note
1. In automated mounting of the SMD sound transducers on PCB, any bending, expanding or pulling forces, or shocks against the SMD sound transducers should be kept to a minimum to prevent them from electrical failures and mechanical damage of the devices.
 2. In the reflow soldering, soldering temperatures that are above specification and extreme gradients such as rapid heating or cooling may cause electrical failures and mechanical damage to the devices.

Soldering Pattern



Terminal Plate: 2 soldering pads, Tin Plating Brass




soberton inc.

ELECTRO
MAGNETIC
BUZZER

Acoustic Product Specification

Product Number: ST-1203T



Release | Revision: A / 2026

CONTENTS

This document contains the technical specifications for the electromagnetic buzzer.

Page 1
Specifications

Dimensions

Page 2
Reliability Test

Page 3
Electrical And Acoustical Measuring Condition



Typical Frequency Response Curve

Page 4
Surface Mounting Condition

Soldering Pattern

Page 5
Packing

Packing



- Note:
1. 1000 pcs Per Reel
 2. Total 10 Reels Per Box
 3. Total 10,000 pcs Per Box